


SERVICE MANUAL

DL383DC



CONTENTS

1.	SAFETY PRECAUTIONS	1
2.	PREVENTION OF ELECTRO STATIC DISCHARGE(ESD)TO ELECTROSTATICALLY SENSITIVE(ES)DEVICES	1
3.	CONTROL BUTTON LOCATIONS AND EXPLANATIONS	2
4.	PREVERTION OF STATIC ELECTRICITY DISCHARGE	4
5.	ELECTRICAL CONFIRMATION	5
5.1	VIDEO OUTPUT (LUMINANCE SIGNAL) CONFIRMATION	5
5.2	VIDEO OUTPUT(CHROMINANCE SIGNAL) CONFIRMATION	6
6.	MPEG BOARD CHECK WAVEFORM	7
7.2	MT1389	8
7.3	HY29LV160	11
7.4	HY57V641620HG	14
8.	SCHEMATIC & PCB WIRING DIAGRAM	17
9.	SPARE PARTS LIST	33

1. SAFETY PRECAUTIONS

1.1 GENERAL GUIDELINES

1. When servicing, observe the original lead dress. If a short circuit is found, replace all parts which have been overheated or damaged by the short circuit.
2. After servicing, see to it that all the protective devices such as insulation barrier, insulation papers shields are properly installed.
3. After servicing, make the following leakage current checks to prevent the customer from being exposed to shock hazards.

2. PREVENTION OF ELECTROSTATIC DISCHARGE(ESD) TO ELECTROSTATICALLY SENSITIVE(ES) DEVICES

Some semiconductor(solid state) devices can be damaged easily by static electricity. Such components commonly are called Electrostatically Sensitive(ES) Devices. Examples of typical ES devices are integrated circuits and some field-effect transistors and semiconductor chip components. The following techniques should be used to help reduce the incidence of component damage caused by electrostatic discharge(ESD).

1. Immediately before handling any semiconductor component or semiconductor-equipped assembly, drain off any ESD on your body by touching a known earth ground. Alternatively, obtain and wear a commercially available discharging ESD wrist strap, which should be removed for potential shock reasons prior to applying power to the unit under test.
2. After removing an electrical assembly equipped with ES devices, place the assembly on a conductive surface such as aluminum foil, to prevent electrostatic charge buildup or exposure of the assembly.
3. Use only a grounded-tip soldering iron to solder or unsolder ES devices.
4. Use only an anti-static solder removal device. Some solder removal devices not classified as anti-static (ESD protected) can generate electrical charge sufficient to damage ES devices.
5. Do not use freon-propelled chemicals. These can generate electrical charges sufficient to damage ES devices.
6. Do not remove a replacement ES device from its protective package until immediately before you are ready to install it. (Most replacement ES devices are packaged with leads electrically shorted together by conductive foam, aluminum foil or comparable conductive material).
7. Immediately before removing the protective material from the leads of a replacement ES device, touch the protective material to the chassis or circuit assembly into which the device will be installed.

Caution

Be sure no power is applied to the chassis or circuit, and observe all other safety precautions.


8. Minimize bodily motions when handling unpackaged replacement ES devices. (Otherwise harmless motion such as the brushing together of your clothes fabric or the lifting of your foot from a carpeted floor can generate static electricity(ESD).

notice (1885x323x2 tiff)

IMPORTANT SAFETY NOTICE


There are special components used in this equipment which are important for safety. These parts are marked by Δ in the schematic diagrams, Exploded Views and replacement parts list. It is essential that these critical parts should be replaced with manufacturer's specified parts to prevent shock, fire or other hazards. Do not modify the original design without permission of manufacturer.

Control Button Locations and Explanations



- | | |
|---|---|
| 1 Color TFT LCD | 13 PLAY button / SELECT button |
| 2 Speakers | 14 NEXT button / RIGHT direction arrow |
| 3 OPEN/CLOSE button | 15 STOP button / UP direction arrow |
| 4 PREV button / LEFT direction arrow | 16 SETUP button |
| 5 PAUSE button / DOWN direction arrow | 17 Browser Button |
| 6 DVD/AUXIN button | 18 PICTURE button |
| 7 Power indicator | 19 POWER Button |
| 8 IR sensor | 20 DVD/READER Button |
| 9 P/N button | 21 MENU Button |
| 10 Panel/Switch Button | |
| 11 Vol-
Adjust the volume of headphone and speaker. | |
| 12 Vol+
Adjust the volume of headphone and speaker. | |

Remote Control Illustration



- 27 MENU Button**
Display DVD menu or open/close PBC.
- 28 A-B Button**
Repeat the select.
- 29 REPEAT Button**
Repeat play.
- 30 RETURN Button**
Back to the previous menu/
Clearing input numbers.
- 31 DVD/READER Button**
- 32 PIC Button**
Set video.
- 33 NUMBER Buttons**
- 34 SUBTITLE Button**
Change subtitle languages/
Switch JPEG display modes.
- 35 OSD Button**
Display or hide disc information.

- 1 STANDBY Button**
Press once to stand by, Press twice to play.
- 2 AUDIO Button**
Change the audio language or audio channel.
- 3 GOTO button**
Play from the desired location.
- 4 ZOOM Button**
Zoom in /out the displayed frame.
- 5 ANGLE Button**
Change camera angles, MP3/JPEG playback modes switch.
- 6 MUTE button**
Press once to mute, twice to unmute.
- 7 TITLE button**
DVD titles.
- 8 CURSOR Buttons**
- 9 SELECT Button**
- 10 SETUP Button**
Function setup.
- 11 PLAY Button**
Normal playback.
- 12 STOP Button**
Stop playback.
- 13 REW Button**
Fast backward play.
- 14 FWD Button**
Fast forward play.
- 15 KEY⏮ Button**
Fall tone.
- 16 KEY⏭ Button**
Rise tone.
- 17 P/N Button**
Switch the TV system between PAL, NTSC and AUTO.
- 18 BROWSER**
Switch new user interface.
- 19 SF Button**
Adjusting sound field effects.
- 20 EQ Button**
Adjusting equalization effects.
- 21 VOLUME-**
Decrease volume.
- 22 VOLUME+**
Increase volume.
- 23 PREV Button**
Skip backward.
- 24 NEXT Button**
Skip forward.
- 25 PAUSE/STEP Button**
Pause or play frame by frame.
- 26 SLOW Button**
Slow play.

4. PREVENTION OF STATIC ELECTRICITY DISCHARGE

The laser diode in the traverse unit (optical pickup) may break down due to static electricity of clothes or human body. Use due caution to electrostatic breakdown when servicing and handling the laser diode.

4.1. Grounding for electrostatic breakdown prevention


Some devices such as the DVD player use the optical pickup (laser diode) and the optical pickup will be damaged by static electricity in the working environment. Proceed servicing works under the working environment where grounding works is completed.

4.1.1. Worktable grounding

1. Put a conductive material (sheet) or iron sheet on the area where the optical pickup is placed, and ground the sheet.

4.1.2. Human body grounding

- 1 Use the anti-static wrist strap to discharge the static electricity from your body.



4.1.3. Handling of optical pickup

1. To keep the good quality of the optical pickup maintenance parts during transportation and before installation, the both ends of the laser diode are short-circuited. After replacing the parts with new ones, remove the short circuit according to the correct procedure. (See this Technical Guide).
2. Do not use a tester to check the laser diode for the optical pickup. Failure to do so will damage the laser diode due to the power supply in the tester.

4.2. Handling precautions for Traverse Unit (Optical Pickup)

1. Do not give a considerable shock to the traverse unit (optical pickup) as it has an extremely high-precision structure.
2. When replacing the optical pickup, install the flexible cable and cut its short lead with a nipper. See the optical pickup replacement procedure in this Technical Guide. Before replacing the traverse unit, remove the short pin for preventing static electricity and install a new unit. Connect the connector as short times as possible.
3. The flexible cable may be cut off if an excessive force is applied to it. Use caution when handling the cable.
4. The half-fixed resistor for laser power adjustment cannot be adjusted. Do not turn the resistor.

5.Electrical Confirmation


5.1. Video Output (Luminance Signal) Confirmation

DO this confirmation after replacing a P.C.B.

Measurement point	Mode	Disc
Video output terminal	Color bar 75% PLAY(Title 46):DVDT-S15 PLAY(Title 12):DVDT-S01	DVDT-S15 or DVDT-S01
Measuring equipment,tools	Confirmation value	
200mV/dir,10 μ sec/dir	1000mVp-p±30mV	

Purpose:To maintain video signal output compatibility.

- 1.Connect the oscilloscope to the video output terminal and terminate at 75 ohms.
- 2.Confirm that luminance signal(Y+S)level is 1000mVp-p±30mV




5.2 Video Output(Chrominance Signal) Confirmation

Do the confirmation after replacing P.C.B.

Measurement point	Mode	Disc
Video output terminal	Color bar 75% PLAY(Title 46):DVDT-S15 PLAY(Title 12):DVDT-S01	DVDT-S15 or DVDT-S01
Measuring equipment,tools	Confirmation value	
Screwdriver,Oscilloscope 200mV/dir,10 μ sec/dir	621mVp-p $\pm$ 30mV	


Purpose:To maintain video signal output compatibility.

- 1.Connect the oscilloscope to the video output terminal and terminate at 75 ohme.
- 2.Confirm that the chrominance signal(C)level is 621 mVp-p $\pm$ 30mV



6.MPEG BOARD CHECK WAVEFORM

6.1 27MHz WAVEFORM



7.2 MT1389

MT1389


Progressive-Scan DVD Player SOC

Specifications are subject to change without notice

MediaTek MT1389 is a DVD player system-on-chip (SOC) which incorporates advanced features like high quality TV encoder and state-of-art de-interlace processing. The MT1389 enables consumer electronics manufacturers to build high quality, cost-effective DVD players, portable DVD players or any other home entertainment audio/video devices.

Based on MediaTek's world-leading DVD player SOC architecture, the MT1389 is the 3rd generation of the DVD player SOC. It integrates the MediaTek 2nd generation front-end analog RF amplifier and the Servo/MPEG AV decoder.

The progressive scan of the MT1389 utilized a proprietary advanced motion-adaptive de-interlace algorithm to achieve the best movie/video playback. It can easily detect 3:2/2:2 pull down source and restore the correct original pictures. It also supports a patent-pending edge-preserving algorithm to remove the saw-tooth effect.



DVD Player System Diagram Using MT1389

Key Features

- RF/Servo/MPEG Integration
- High Performance Audio Processor
- Motion-Adaptive, Edge-Preserving De-interlace
- 108MHz/12-bit, 6 CH TV Encoder

Applications

- Standard DVD Players
- Portable DVD Players

General Feature List

- Super Integration DVD player single chip
 - High performance analog RF amplifier
 - Servo controller and data channel processing
 - MPEG-1/MPEG-2/JPEG video
 - Dolby AC-3/DTS/DVD-Audio
 - Unified memory architecture
 - Versatile video scaling & quality enhancement
 - OSD & Sub-picture
 - 2-D graphic engine
 - Built-in clock generator
 - Built-in high quality TV encoder
 - Built-in progressive video processor
 - Audio effect post-processor
 - Audio input port
- High Performance Analog RF Amplifier
 - Programmable fc
 - Dual automatic laser power control
 - Defect and blank detection
 - RF level signal generator
- Speed Performance on Servo/Channel Decoding
 - DVD-ROM up to 4XS
 - CD-ROM up to 24XS
- Channel Data Processor
 - Digital data slicer for small jitter capability
 - Built-in high performance data PLL for channel data demodulation
 - EFM/EFM+ data demodulation
 - Enhanced channel data frame sync protection & DVD-ROM sector sync protection
- Servo Control and Spindle Motor Control
 - Programmable frequency error gain and phase error gain of spindle PLL to control spindle motor on CLV and CAV mode
 - Built-in ADCs and DACs for digital servo control
 - Provide 2 general PWM
 - Tray control can be PWM output or digital output
- Embedded Micro controller
 - Built-in 8032 micro controller
 - Built-in internal 373 and 8-bit programmable lower address port
- 1024-bytes on-chip RAM
- Up to 4M bytes FLASH-programming interface
- Supports 5/3.3-Volt. FLASH interface
- Supports power-down mode
- Supports additional serial port
- DVD-ROM/CD-ROM Decoding Logic
 - High-speed ECC logic capable of correcting one error per each P-codeword or Q-codeword
 - Automatic sector Mode and Form detection
 - Automatic sector Header verification
 - Decoder Error Notification Interrupt that signals various decoder errors
 - Provide error correction acceleration
- Buffer Memory Controller
 - Supports 16Mb/32Mb/64Mb/128Mb SDRAM
 - Supports 16-bit SDRAM data bus
 - Provide the self-refresh mode SDRAM
 - Block-based sector addressing
 - Support 3.3 Volt. DRAM Interface
- Video Decode
 - Decodes MPEG1 video and MPEG2 main level, main profile video (720/480 and 720x576)
 - Smooth digest view function with I, P and B picture decoding
 - Baseline, extended-sequential and progressive JPEG image decoding
 - Support CD-G titles
- Video/OSD/SPU/HLI Processor
 - Arbitrary ratio vertical/horizontal scaling of video, from 0.25X to 256X
 - 65535/256/16/4/2-color bitmap format OSD,
 - 256/16 color RLC format OSD
 - Automatic scrolling of OSD image
 - Slide show transition as DVD-Audio Specification
- 2-D Graphic Engine
 - Support decode Text and Bitmap
 - Support line, rectangle and gradient fill
 - Support bitblt
 - Chroma key copy operation
 - Clip mask

- Audio Effect Processing
 - Dolby Digital (AC-3)/EX decoding
 - DTS/DTS-ES decoding
 - MLP decoding for DVD-Audio
 - MPEG-1 layer 1/layer 2 audio decoding
 - MPEG-2 layer1/layer2 2-channel audio
 - High Definition Compatible Digital (HDCD)
 - Windows Media Audio (WMA)
 - Advanced Audio Coding (AAC)
 - Dolby ProLogic II
 - Concurrent multi-channel and downmix out
 - IEC 60958/61937 output
 - PCM / bit stream / mute mode
 - Custom IEC latency up to 2 frames
 - Pink noise and white noise generator
 - Karaoke functions
 - Microphone echo
 - Microphone tone control
 - Vocal mute/vocal assistant
 - Key shift up to +/- 8 keys
 - Chorus/Flanger/Harmony/Reverb
 - Channel equalizer
 - 3D surround processing include virtual surround and speaker separation
- TV Encoder
 - Six 108MHz/12bit DACs
 - Support NTSC, PAL-BDGHINM, PAL-60
 - Support 525p, 625p progressive TV format
 - Automatically turn off unconnected channels
 - Support PC monitor (VGA)
 - Support Macrovision 7.1 L1, Macrovision 525P and 625P
 - CGMS-A/WSS
 - Closed Caption
- Progressive Output
 - Automatic detect film or video source
 - 3:2 pull down source detection
 - Advanced Motion adaptive de-interlace
 - Edge Preserving
 - Minimum external memory requirement
- Audio Input
 - Line-in/SPDIF-in for versatile audio processing
- Outline
 - 256-pin LQFP package
 - 3.3/1.8-Volt. Dual operating voltages

IC BLOCK DIAGRAM & DESCRIPTION




HY29LV160
16 Mbit (2M x 8/1M x 16) Low Voltage Flash Memory

KEY FEATURES

- **Single Power Supply Operation**
 - Read, program and erase operations from 2.7 to 3.6 volts
 - Ideal for battery-powered applications
- **High Performance**
 - 70, 80, 90 and 120 ns access time versions
- **Ultra-low Power Consumption (Typical Values At 5 Mhz)**
 - Automatic sleep mode current: 1 μ A
 - Standby mode current: 1 μ A
 - Read current: 9 mA
 - Program/erase current: 20 mA
- **Flexible Sector Architecture:**
 - One 16 KB, two 8 KB, one 32 KB and thirty-one 64 KB sectors in byte mode
 - One 8 KW, two 4 KW, one 16 KW and thirty-one 32 KW sectors in word mode
 - Top or bottom boot block configurations available
- **Sector Protection**
 - Allows locking of a sector or sectors to prevent program or erase operations within that sector
 - Sectors lockable in-system or via programming equipment
 - Temporary Sector Unprotect allows changes in locked sectors (requires high voltage on RESET# pin)
- **Fast Program and Erase Times**
 - Sector erase time: 0.25 sec typical for each sector
 - Chip erase time: 8 sec typical
 - Byte program time: 9 μ s typical
- **Unlock Bypass Program Command**
 - Reduces programming time when issuing multiple program command sequences
- **Automatic Erase Algorithm Preprograms and Erases Any Combination of Sectors or the Entire Chip**
- **Erase Suspend/Erase Resume**
 - Suspends an erase operation to allow reading data from, or programming data to, a sector that is not being erased
 - Erase Resume can then be invoked to complete suspended erasure
- **Automatic Program Algorithm Writes and Verifies Data at Specified Addresses**
- **100,000 Write Cycles per Sector Minimum**
- **Data# Polling and Toggle Bits**
 - Provide software confirmation of completion of program and erase operations
- **Ready/Busy# Pin**
 - Provides hardware confirmation of completion of program and erase operations
- **Hardware Reset Pin (RESET#) Resets the Device to Reading Array Data**
- **Compliant With Common Flash Memory Interface (CFI) Specification**
 - Flash device parameters stored directly on the device
 - Allows software driver to identify and use a variety of different current and future Flash products
- **Compatible With JEDEC standards**
 - Pinout and software compatible with single-power supply Flash devices
 - Superior inadvertent write protection
- **Space Efficient Packaging**
 - 48-pin TSOP and 48-ball FBGA packages

LOGIC DIAGRAM




IC BLOCK DIAGRAM & DESCRIPTION

HY29LV160



BLOCK DIAGRAM





SIGNAL DESCRIPTIONS

Name	Type	Description
A[19:0]	Inputs	Address, active High. These 20 inputs, combined with the DQ[15]/A[-1] input in Byte mode, select one location within the array for read or write operations.
DQ[15]/A[-1], DQ[14:0]	Inputs/Outputs Tri-state	Data Bus, active High. These pins provide an 8- or 16-bit data path for read and write operations. In Byte mode, DQ[15]/A[-1] is used as the LSB of the 21-bit byte address input. DQ[14:8] are unused and remain tri-stated in Byte mode.
BYTE#	Input	Byte Mode, active Low. Low selects Byte mode, High selects Word mode.
CE#	Input	Chip Enable, active Low. This input must be asserted to read data from or write data to the HY29LV160. When High, the data bus is tri-stated and the device is placed in the Standby mode.
OE#	Input	Output Enable, active Low. Asserted for read operations and negated for write operations. BYTE# determines whether a byte or a word is read during the read operation.
WE#	Input	Write Enable, active Low. Controls writing of commands or command sequences in order to program data or erase sectors of the memory array. A write operation takes place when WE# is asserted while CE# is Low and OE# is High.
RESET#	Input	Hardware Reset, active Low. Provides a hardware method of resetting the HY29LV160 to the read array state. When the device is reset, it immediately terminates any operation in progress. While RESET# is asserted, the device will be in the Standby mode.
RY/BY#	Output Open Drain	Ready/Busy Status. Indicates whether a write or erase command is in progress or has been completed. Remains Low while the device is actively programming data or erasing, and goes High when it is ready to read array data.
V _{CC}	--	3-volt (nominal) power supply.
V _{SS}	--	Power and signal ground.

IC BLOCK DIAGRAM & DESCRIPTION

PIN CONFIGURATIONS

48-Ball FBGA (Bottom View)



7.4 HY57V641620HG

DESCRIPTION

The Hyundai HY57V641620HG is a 67,108,864-bit CMOS Synchronous DRAM, ideally suited for the main memory applications which require large memory density and high bandwidth. HY57V641620HG is organized as 4banks of 1,048,576x16.


HY57V641620HG is offering fully synchronous operation referenced to a positive edge of the clock. All inputs and outputs are synchronized with the rising edge of the clock input. The data paths are internally pipelined to achieve very high bandwidth. All input and output voltage levels are compatible with LVTTL.

Programmable options include the length of pipeline (Read latency of 2 or 3), the number of consecutive read or write cycles initiated by a single control command (Burst length of 1,2,4,8 or Full page), and the burst count sequence(sequential or interleave). A burst of read or write cycles in progress can be terminated by a burst terminate command or can be interrupted and replaced by a new burst read or write command on any cycle. (This pipelined design is not restricted by a `2N` rule.)

FEATURES

- Single 3.3±0.3V power supply ^{Note)}
- All device pins are compatible with LVTTL interface
- JEDEC standard 400mil 54pin TSOP-II with 0.8mm of pin pitch
- All inputs and outputs referenced to positive edge of system clock
- Data mask function by UDQM or LDQM
- Internal four banks operation
- Auto refresh and self refresh
- 4096 refresh cycles / 64ms
- Programmable Burst Length and Burst Type
 - 1, 2, 4, 8 or Full page for Sequential Burst
 - 1, 2, 4 or 8 for Interleave Burst
- Programmable $\overline{\text{CAS}}$ Latency ; 2, 3 Clocks

PIN CONFIGURATION




PIN DESCRIPTION

PIN	PIN NAME	DESCRIPTION
CLK	Clock	The system clock input. All other inputs are registered to the SDRAM on the rising edge of CLK
CKE	Clock Enable	Controls internal clock signal and when deactivated, the SDRAM will be one of the states among power down, suspend or self refresh
$\overline{CS}$	Chip Select	Enables or disables all inputs except CLK, CKE and DQM
BA0,BA1	Bank Address	Selects bank to be activated during $\overline{RAS}$ activity Selects bank to be read/written during CAS activity
A0 ~ A11	Address	Row Address : RA0 ~ RA11, Column Address : CA0 ~ CA7 Auto-precharge flag : A10
$\overline{RAS}$, $\overline{CAS}$, $\overline{WE}$	Row Address Strobe, Column Address Strobe, Write Enable	$\overline{RAS}$, $\overline{CAS}$ and $\overline{WE}$ define the operation Refer function truth table for details
LDQM, UDQM	Data Input/Output Mask	Controls output buffers in read mode and masks input data in write mode
DQ0 ~ DQ15	Data Input/Output	Multiplexed data input / output pin
VDD/VSS	Power Supply/Ground	Power supply for internal circuits and input buffers
VDDQ/VSSQ	Data Output Power/Ground	Power supply for output buffers
NC	No Connection	No connection


FUNCTIONAL BLOCK DIAGRAM

1Mbit x 4banks x 16 I/O Synchronous DRAM



8.SCHEMATIC & P.C.B WIRING DIAGRAM


DECODE BOARD





更改		数量		变更单号		签 名		日期	
设计		审核		批准		批 准		批 准	
标准		审核		批准		批 准		批 准	
批 准		批 准		批 准		批 准		批 准	


更改		数量		变更单号		签 名		日期	
设计		审核		批准		批 准		批 准	
标准		审核		批准		批 准		批 准	
批 准		批 准		批 准		批 准		批 准	

更改		数量		变更单号		签 名		日期	
设计		审核		批准		批 准		批 准	
标准		审核		批准		批 准		批 准	
批 准		批 准		批 准		批 准		批 准	












Title		Revision	
Size	Number		
B	B		
Date:	19-Jan-2005	Sheet of	5
File:	D:\DL 353D\L353D\CS.ddb	Drawn By:	6

DECODE BOARD








BATTERY CHARGER



MAIN FRONT PANEL




LCD DRIVE BOARD




SZ MPEG ELECTRONIC CO.,LTD			
File	松 T-TFT DRIVER BOARD	Rev	1
Size	Document Number	AN2546	
Date	Tuesday, December 30, 2004	Sheet	1 of 3

LCD DRIVE BOARD




SZ MPEG ELECTRONIC CO.,LTD			
File	松下-TFT DRIVER BOARD	Sheet	2 of 3
Size	Document Number	Rev	1
Date	Thursday, December 30, 2004	Sheet	2 of 3

LCD DRIVE BOARD




BOOST BOARD




REV	DATE	DESCRIPTION	BY	CHK	APPV	DATE	REV	DATE	DESCRIPTION	BY	CHK	APPV	DATE
1	11/20/93	Revision Sheet					1	11/20/93	Revision Sheet				
2	11/20/93	Schematic Diagram					2	11/20/93	Schematic Diagram				
3	11/20/93	3DA01184X					3	11/20/93	3DA01184X				
4	11/20/93	3DA01184X					4	11/20/93	3DA01184X				
5	11/20/93	3DA01184X					5	11/20/93	3DA01184X				
6	11/20/93	3DA01184X					6	11/20/93	3DA01184X				
7	11/20/93	3DA01184X					7	11/20/93	3DA01184X				
8	11/20/93	3DA01184X					8	11/20/93	3DA01184X				
9	11/20/93	3DA01184X					9	11/20/93	3DA01184X				
10	11/20/93	3DA01184X					10	11/20/93	3DA01184X				
11	11/20/93	3DA01184X					11	11/20/93	3DA01184X				
12	11/20/93	3DA01184X					12	11/20/93	3DA01184X				
13	11/20/93	3DA01184X					13	11/20/93	3DA01184X				
14	11/20/93	3DA01184X					14	11/20/93	3DA01184X				
15	11/20/93	3DA01184X					15	11/20/93	3DA01184X				
16	11/20/93	3DA01184X					16	11/20/93	3DA01184X				
17	11/20/93	3DA01184X					17	11/20/93	3DA01184X				
18	11/20/93	3DA01184X					18	11/20/93	3DA01184X				
19	11/20/93	3DA01184X					19	11/20/93	3DA01184X				
20	11/20/93	3DA01184X					20	11/20/93	3DA01184X				
21	11/20/93	3DA01184X					21	11/20/93	3DA01184X				
22	11/20/93	3DA01184X					22	11/20/93	3DA01184X				
23	11/20/93	3DA01184X					23	11/20/93	3DA01184X				
24	11/20/93	3DA01184X					24	11/20/93	3DA01184X				
25	11/20/93	3DA01184X					25	11/20/93	3DA01184X				
26	11/20/93	3DA01184X					26	11/20/93	3DA01184X				
27	11/20/93	3DA01184X					27	11/20/93	3DA01184X				
28	11/20/93	3DA01184X					28	11/20/93	3DA01184X				
29	11/20/93	3DA01184X					29	11/20/93	3DA01184X				
30	11/20/93	3DA01184X					30	11/20/93	3DA01184X				
31	11/20/93	3DA01184X					31	11/20/93	3DA01184X				


Top Overlay



TopLayer



BottomLayer

[illegible]

PARTS LIST

IDX. CD.		XAD184NF					
184X							
PART NUMBER		DESCRIPTION	QUANT	ITEM NO.	MFRS.	INS.	
C1	C4532X5R1C226MT000N	CAPACITOR	1	IN27200303	TDK		
C2	C1608X7R1E103KT000N OR C1608X7R1H103KT000N	CAPACITOR	1	IN01605301 IN01603601	TDK TDK		
C3	C1608X7R1E104KT000N OR C1608X7R1H104KT000N	CAPACITOR	1	IN01618702 IN01661801	TDK TDK		
C4	C2012X7R1E105KT000N OR C2012X7R1C105KT000N	CAPACITOR	1	IN30626701 UN30652203	TDK TDK		
C5	C1608X7R1E104KT000N OR C1608X7R1H104KT000N	CAPACITOR	1	IN01618702 IN01661801	TDK TDK		
C6	C1608X7R1E103KT000N OR C1608X7R1H103KT000N	CAPACITOR	1	IN01605301 IN01603601	TDK TDK		
C7	C1608Y5V1C105ZT000N OR C1608X5R1C105KT000N	CAPACITOR	1	IN30300701 IN30205102	TDK TDK		
C8	C2012X7R1E105KT000N OR C2012X7R1C105KT000N	CAPACITOR	1	IN30626701 IN30652203	TDK TDK		
C10	C1608X7R1E152KT000N OR C1608X7R1H152KT000N	CAPACITOR	1	IN01650801 IN01671801	TDK TDK		
C11	C1608X7R1E103KT000N OR C1608X7R1H103KT000N	CAPACITOR	1	IN01605301 IN01603601	TDK TDK		
C12	C1608Y5V1C105ZT000N OR C1608X5R1C105KT000N	CAPACITOR	1	IN30300701 IN30205102	TDK TDK		
C13	C2012X7R1C474KT000N OR C2012X7R1E474KT000N	CAPACITOR	1	IN30602604 IN30608002	TDK TDK		
C14	C2012X7R1C474KT000N OR C2012X7R1E474KT000N	CAPACITOR	1	IN30602604 IN30608002	TDK TDK		
C15	C1608X7R1E104KT000N OR C1608X7R1H104KT000N	CAPACITOR	1	IN01618702 IN01661801	TDK TDK		
C16	302R29N150JV4E OR C4520C0G3F150JT0A0N	CAPACITOR	1		JOHANSON TDK		
C17	C1608X7R1E683KT000N OR C1608X7R1H683KT000N	CAPACITOR	1	NS13006 IN58801200	TKD TDK		
C18	NA						
C19	C1608X7R1E562KT000N OR C1608X7R1H562KT000N	CAPACITOR	1	IN01674801 IN01670201	TDK TDK		
C20	NA						
C21	C1608X7R1E103KT000N OR C1608X7R1H103KT000N	CAPACITOR	1	IN01605301 IN01603601	TDK TDK		
R2	RC0603FRF10K OR RMC16P1002F	RESISTOR	1	NS06033 NS06494	YAGEO KAMAYA		
R4	RC0603FRF4.3K OR RMC16P4301F	RESISTOR	1	NS06165 NS06552	YAGEO KAMAYA		
				TITLE: ELECTRICAL PARTS LIST			
				MODEL: XAD184NF			
				DESIGNED	Jiaxiong Shen	DATE	
				DRAWN	Jiaxiong Shen	01/30/04	
				CHECKED		/ /	
REV.	DATE	DESCRIPTION	DRAWN	APV.	APPVD.	/ /	
TDK XIAMEN CO., LTD. POWER MFG. DEPT. 321-329, Tongji South RD., Jimei Dist., Xiamen, Fujian, P.R.China			DATE	APPVD.	/ /		
				DWG. NO.	4CA01184X		PAGE
					1/2		

BOOST BOARD

PARTS LIST

IDX. CD.		XAD184NF					
184X							
PART NUMBER		DESCRIPTION	QUANT	ITEM NO.	MFRS.	INS.	
R6	RC0603FRF100K OR RMC16P1003F	RESISTOR	1	NS06028 NS06514	YAGEO KAMAYA		
R8	RC0603FRF300K OR RMC16P3003F	RESISTOR	1	NS06163 NS06527	YAGEO KAMAYA		
R10	RC0603FRF0R0 OR RMC16P0R00	RESISTOR	1	NS06168 NS06481	YAGEO KAMAYA		
R11	RC0603FRF100K OR RMC16P1003F	RESISTOR	1	NS06028 NN06541	YAGEO KAMAYA		
R12	RC0603FRF1K OR RMC16P1001F	RESISTOR	1	NS06020 NS06502	YAGEO KAMAYA		
R13	RC0603FRF300K OR RMC16P3003F	RESISTOR	1	NS06163 NS06527	YAGEO KAMAYA		
R14	RC0603FRF4.3K OR RMC16P4301F	RESISTOR	1	NS06165 NS06552	YAGEO KAMAYA		
R15	RC0603FRF200R OR RMC16P2000F	RESISTOR	1	NS06219 NS06584	YAGEO KAMAYA		
R16	RC0603FRF2K OR RMC16P2001F	RESISTOR	1	NS06113 NS06531	YAGEO KAMAYA		
T1	TDK 10U1-X12	TRANSFORMER	1		GUANN JYE		
IC1	MP1010BEM MP1015EM	IC	1	NS35008 NS35004	MPS		
PB1	3EA02184X 02	P.W.B.	1		MILKY-WAY CCTC XINE		
F1	CCP2E63 TE	FUSE	1		KOA		
CN1	8680S-0300	CONNECTOR	1		E&T		
CN2	4100-02 SM02B-BHSS-1-TB	CONNECTOR	1		E&T ACES		
	4EU02184X	CABLE	1		TDK		
CR1	1SS226(TE85L) MA157-TX	DIODE	1		TOSHIBA PANASONIC		
Packaging Parts List Refer to 4CC12073X Packaging Darling Refer to 4LC12073X							
				TITLE: ELECTRICAL PARTS LIST			
				MODEL: XAD184NF			
				DESIGNED		DATE / /	
				DRAWN		/ /	
				CHECKED		/ /	
REV.	DATE	DESCRIPTION	DRAWN	APV.	APPVD.		/ /
TDK XIAMEN CO., LTD. POWER MFG. DEPT. 321~339, Tongji South RD., Jinmei Dist., Xiamen, Fujian, P.R.China			DATE	APPVD.		/ /	
				DWG. NO.			PAGE
				4CA01184X			2/2

9.DVDPX-I80S MATERIAL

DL383DC MATERIAL LIST

1. MAIN PANEL

MATERIAL CODE	MATERIAL NAME	SPECIFICATIONS	UNIT	QUANTITY	LOCATION
0090001	SMD RESISTOR	1/16W 0Ω ±5% 0603	PCS	1	R403
0310084	SMD CAPACITOR	50V 104 +80%-20% 0603	PCS	1	C401
0310048	SMD CAPACITOR	50V 151 ±5% NPO 0603	PCS	2	C402,C403
0310376	SMD TANTIUM CAPACITOR	NRS10V47U±20%3528(B2)	PCS	1	TC401
0700002	SMD DIODE	LL4148	PCS	3	VD401,VD402,VD403
0700001	SMD DIODE	LS4148	PCS	3	VD401,VD402,VD403
0700007	SMD DIODE	1N4148	PCS	3	VD401,VD402,VD403
0970003	CERAMIC RESONATOR	455E	PCS	1	X401
0881587	IC	PT2222A SOP	PCS	1	U401
1940150	SOCKET	4P 1.0mm SMD	PCS	1	XS401
0780129	SMD TRIODE	8550D	PCS	1	V401
0090023	SMD RESISTOR	1/16W 10K ±5% 0603	PCS	1	R401
1631948	PCB	4383-2	PCS	1	

2. SWITCH BOARD

MATERIAL CODE	MATERIAL NAME	SPECIFICATIONS	UNIT	QUANTITY	LOCATION
1350053	TESTING SWITCH	SPVE110600	PCS	1	SW901
1940150	SOCKET	4P 1.0mm SMD	PCS	1	XS901
1563558	PCB	9383-4	PCS	1	

3. LCD DRIVE BOARD

MATERIAL CODE	MATERIAL NAME	SPECIFICATIONS	UNIT	QUANTITY	LOCATION
0090001	SMD RESISTOR	1/16W 0Ω ±5% 0603	PCS	9	R100,R25,R21,R70,R73,R22, R37,R27,R62
0090003	SMD RESISTOR	1/16W 10Ω ±5% 0603	PCS	1	R97
0090006	SMD RESISTOR	1/16W 75Ω ±5% 0603	PCS	2	R94,R98
0090181	SMD RESISTOR	1/16W 100Ω ±5% 0603	PCS	3	R48,R50,R6
0090009	SMD RESISTOR	1/16W 330Ω ±5% 0603	PCS	1	R80
0090014	SMD RESISTOR	1/16W 1K ±5% 0603	PCS	6	R18,R19,R90,R91,R96,R117
0090017	SMD RESISTOR	1/16W 2.2K ±5% 0603	PCS	2	R11,R78
0090254	SMD RESISTOR	1/16W 9.1K ±5% 0603	PCS	1	R51
0090018	SMD RESISTOR	1/16W 3.3K ±5% 0603	PCS	4	R28,R29,R34,R83
0090019	SMD RESISTOR	1/16W 4.7K ±5% 0603	PCS	3	R2,R3,R12
0090225	SMD RESISTOR	1/16W 5.6K ±5% 0603	PCS	4	R74,R75,R76,R77
0090023	SMD RESISTOR	1/16W 10K ±5% 0603	PCS	7	R17,R58,R60,R82,R79,R116, R118
0090024	SMD RESISTOR	1/16W 15K ±5% 0603	PCS	3	R52,R86,R88
0090026	SMD RESISTOR	1/16W 22K ±5% 0603	PCS	3	R14,R59,R49
0090028	SMD RESISTOR	1/16W 33K ±5% 0603	PCS	3	R87,R89,R57
0090029	SMD RESISTOR	1/16W 47K ±5% 0603	PCS	2	R13,R56
0090030	SMD RESISTOR	1/16W 56K ±5% 0603	PCS	2	R53,R54
0090032	SMD RESISTOR	1/16W 68K ±5% 0603	PCS	3	R10,R16,R81
0090034	SMD RESISTOR	1/16W 100K ±5% 0603	PCS	2	R63,R67
0090199	SMD RESISTOR	1/16W 180K ±5% 0603	PCS	2	R55,R66
0090205	SMD RESISTOR	1/16W 330K ±5% 0603	PCS	2	R65,R26
0090208	SMD RESISTOR	1/16W 470K ±5% 0603	PCS	1	R20
0090109	SMD RESISTOR	1/16W 1MΩ ±5% 0603	PCS	2	R15,R84
0160156	SMD ROTATED POTENTIOMETER	W203-50K±20%	PCS	1	VR1
0310042	SMD CAPACITOR	50V 15P ±5% NPO 0603	PCS	1	C80
0310188	SMD CAPACITOR	50V 10P ±5% NPO 0603	PCS	1	C81
0310190	SMD CAPACITOR	50V 27P ±5% NPO 0603	PCS	1	C98
0310086	SMD CAPACITOR	50V 39P ±5% NPO 0603	PCS	1	C72
0310192	SMD CAPACITOR	50V 56P ±5% NPO 0603	PCS	1	C20
0310049	SMD CAPACITOR	50V 221 ±5% NPO 0603	PCS	1	C43
0310053	SMD CAPACITOR	50V 471 ±5% NPO 0603	PCS	1	C44
0310471	SMD CAPACITOR	50V 561±5% NPO 0603	PCS	1	C15
0310066	SMD CAPACITOR	50V 102 ±10% 0603	PCS	3	C16,C42,C84
0310072	SMD CAPACITOR	50V 103 ±10% 0603	PCS	2	C40,C50
0310202	SMD CAPACITOR	50V 223 ±10% 0603	PCS	2	C78,C87
0310205	SMD CAPACITOR	50V 473 ±10% 0603	PCS	1	C88
0310594	SMD CAPACITOR	25V 104 ±10% 0603	PCS	36	C2,C4,C6,C8,C10,C11,C12,C 13,C14,C17,C18,C45,C48,C4 9,C60,C69,C75,C95,C83,C89, C93,C94,C96,C97,C35,C102, C62,C76,C56,C57,C58,C66,C 67,C73,C74,C77

0310362	SMD CAPACITOR	16V474 +80%-20% 0603	PCS	1	C86
0310216	SMD CAPACITOR	10V 105 +80%-20% 0603	PCS	10	C21,C39,C53,C54,C55,C64,C65,C79,C85,C91
0310364	SMD CAPACITOR	10V 225 +80%-20% 0805	PCS	4	C47,C51,C52,C70
0310461	SMD CAPACITOR	10V 475+80%-20% 0805	PCS	2	C90,C92
0310219	SMD CAPACITOR	16V 106 +80%-20% 1206	PCS	3	C34,C41,C99
0310577	SMD CERAMIC CAPACITOR	10V 226 +80% -20% 1206	PCS	2	C59,C71
0310549	SMD CERAMIC CAPACITOR	25V 106+80%-20% 1210	PCS	5	C1,C3,C19,C36,C101
0310376	SMD TANTIUM CAPACITOR	NRS10V47U±20%3528(B2)	PCS	10	C5,C7,C9,C37,C63,C68,C100,C103,C61,C82
0390296	SMD INDUCTOR	1.5UH ±10% 3216	PCS	1	L7
0390044	SMD INDUCTOR	10UH ±10% 2012	PCS	7	L1,L2,L3,L4,L5,L12,L13
0090036	SMD RESISTOR	1/10W 0Ω ±5% 0805	PCS	1	L15
0390215	SMD INDUCTOR	33uH±10% 3225	PCS	2	LP2,L14
0680028	SMD SCHOTTKY DIODE	MBRS340	PCS	2	D1,D2
0700007	SMD DIODE	1N4148	PCS	1	D4
0700052	SMD DIODE	MA335	PCS	1	D3
0700116	SMD VOLTAGE REGULATOR DIO	3V 1/2W 5mA SOD80C	PCS	1	D5
0780040	SMD TRIODE	3904	PCS	9	Q3,Q4,Q5,Q6,Q7,Q8,Q9,Q10,Q104
0780129	SMD TRIODE	8550D	PCS	2	Q2,Q12
0780085	SMD TRIODE	8050D	PCS	2	Q1,Q11
0881826	IC	AN2546FH QFP	PCS	1	U1
0881827	IC	MN5814-3 QFP	PCS	1	U2
0880157	IC	74HC4066 SOP	PCS	1	U9
0882049	IC	TDA4665T SOP	PCS	1	U5
0882050	IC	LMC7101 SOT23-5	PCS	1	U8
0882051	IC	NJM2082 SOP	PCS	1	U7
0882114	IC	AMS1117-3.3 SOT-223	PCS	1	ICP2
0960213	SMD CRYSTAL OSCILLATOR	4.43MHz 49-S	PCS	1	Y2
0960212	SMD CRYSTAL OSCILLATOR	3.58MHz 49-S	PCS	1	Y1
1940208	CABLE SOCKET	30P 0.5mm SMD WITH CLASP	PCS	1	J3
1940205	SOCKET	16P 1.0mm SMD	PCS	1	J1
0390302	SMD MAGNETIC BEADS	MGHB1608S102	PCS	3	R23,R30,R31
1631643	PCB	C383-2	PCS	1	

3. BATTERY CHARGER

MATERIAL CODE	MATERIAL NAME	SPECIFICATIONS	UNIT	QUANTITY	LOCATION
0090019	SMD RESISTOR	1/16W 4.7K ±5% 0603	PCS	1	RB41
0090536	SMD RESISTOR	1/8W0.27Ω±5% 1206	PCS	5	R1,R2,R3,R4,R5
0090003	SMD RESISTOR	1/16W 10Ω ±5% 0603	PCS	1	RB6
0090135	SMD RESISTOR	1/8W 100Ω ±5% 1206	PCS	2	RB42,RB44
0090011	SMD RESISTOR	1/16W 470Ω ±5% 0603	PCS	2	RB16,RB48
0090488	SMD RESISTOR	1/8W 470Ω±5% 1206	PCS	3	RB12,RB13,RB5
0090014	SMD RESISTOR	1/16W 1K ±5% 0603	PCS	6	RB10,RB33,RB34,RB35,RB36,RB45
0090171	SMD RESISTOR	1/8W 1K ±5% 1206	PCS	2	RB4,RB9
0090017	SMD RESISTOR	1/16W 2.2K ±5% 0603	PCS	1	RB43
0090236	SMD RESISTOR	1/16W 1.8K ±5% 0603	PCS	1	RB18
0090018	SMD RESISTOR	1/16W 3.3K ±5% 0603	PCS	4	RB8,RB7,RB32,RB31
0090304	PRECISION SMD RESISTOR	1/16W 10K±1% 0603	PCS	2	RB46,RB47
0090023	SMD RESISTOR	1/16W 10K ±5% 0603	PCS	11	RB1,RB2,RB3,RB14,RB22,RB28,RB29,RB30,RB38,RB39,RB40
0090029	SMD RESISTOR	1/16W 47K ±5% 0603	PCS	1	RB15
0090201	SMD RESISTOR	1/16W 220K ±5% 0603	PCS	1	RB11
0090025	SMD RESISTOR	1/16W 20K ±5% 0603	PCS	1	RB17
0090490	PRECISION SMD RESISTOR	1/16W 22K±1% 0603	PCS	2	RB23,RB26
	SMD RESISTOR		PCS		RB24/RB27 MODULATE PARAMETER ON SPOT 1M~4.7M
0090233	SMD RESISTOR	1/16W 4.7MΩ ±5% 0603	PCS	1	RB37
0310594	SMD CAPACITOR	25V 104 ±10% 0603	PCS	4	CB11,CB13,CB19,CB20
0310505	SMD CAPACITOR	25V 224 +80%-20% 0603	PCS	3	CB12,CB14,CB15
0310230	SMD CAPACITOR	50V 474 +80%-20% 0603	PCS	5	CB4,CB5,CB16,CB17,CB18
0310217	SMD CAPACITOR	16V 225 +80%-20% 1206	PCS	3	CB1,CB2,CB10
0260181	CD	CD11 16V220U±20%6×12 C5	PCS	3	CB3,CB6,CB7
0410139	CHOKE COIL	VERTICAL 30UH 3A 15mm	PCS	1	LB1
0780041	SMD TRIODE	3906	PCS	1	QB3

0780276	SMD TRIODE	GS9013 SOT-23	PCS	6	QB2,QB4,QB5,QB10,QB11, QB12
0680050	SMD SCHOTTKY DIODE	MBRS140	PCS	1	DB1
0680028	SMD SCHOTTKY DIODE	MBRS340	PCS	1	DB2
0580034	VOLTAGE REGULATOR DIODE	10V 1W	PCS	1	ZB1
0790021	FIELD EFFECT TUBE	IRF7416 SOP	PCS	1	QB1
0790040	FIELD EFFECT TUBE	UPA1870 SSOP	PCS	1	QB7+8
0790039	FIELD EFFECT TUBE	IRF7316 S08	PCS	1	QB6+9
0882184	IC	S3F9454 SOP(383)	PCS	1	IC1
0881941	IC	S8232AUFT TSSOP	PCS	1	IC3
0880176	IC	LM358M SOP	PCS	1	LM358AM
0882089	IC	TL431 TO-92	PCS	1	IC2
3027181	SPACER	DL373	PCS	1	BETWEEN POWER ADAPTOR AND PCB BOARD
0620032	DUAL-COLOR RADIATION DIODE	2RG 59SW RED AND GREEN 2×5×7	PCS	1	DB3
1870021	POWER SOCKET	DC-023	PCS	1	DCB_IN1
1860044	BATTERY ADAPTOR	4P2.5MM LIN-0402-040-100	PCS	1	TB1
1631668	PCB	B383-2	PCS	1	

4. CAR ADAPTOR

MATERIAL CODE	MATERIAL NAME	SPECIFICATIONS	UNIT	QUANTITY	LOCATION
0090050	SMD RESISTOR	1/10W 1K ±5%	PCS	2	R4,R6
0090479	PRECISION SMD RESISTOR	1/10W 3.9K±1% 0805	PCS	1	R5
0090480	PRECISION SMD RESISTOR	1/10W 24K±1% 0805	PCS	1	R3
0010217	METAL OXIDE FILM RESISTOR	1W0.22Ω±5% SHAPED VERTICAL 5	PCS	1	R2
0010218	METAL OXIDE FILM RESISTOR	1W0.15Ω±5% SHAPED VERTICAL 5	PCS	1	R1
0310144	SMD CAPACITOR	50V 104 ±10% 0805	PCS	4	C4,C5,C7,C8
0310029	SMD CAPACITOR	50V 102 ±10% 0805	PCS	1	C9
0310102	SMD CAPACITOR	50V 471 ±10% 0805	PCS	1	C6
0260370	CD	CD11C 35V100U±20%6.3×11 2.5	PCS	2	C1,C2
0260168	CD	CD11 25V1000U±20%10×20 5	PCS	1	C3
0780085	SMD TRIODE	8050D	PCS	1	V1
0780129	SMD TRIODE	8550D	PCS	1	V2
0881701	IC	MC34063A SOP	PCS	1	U1
0881867	IC	FDS9435A SOP	PCS	1	U2
0620025	RADIATION DIODE	3R 4SD RED	PCS	1	VD2
0390251	VERTICAL INDUCTOR	3UH±10% 12×8.5 5mm	PCS	1	L1
0410131	INDUCTOR COIL	85UH±10% Φ18×8Φ0.8	PCS	1	L2
0680041	SCHOTTKY DIODE	SB560 SHAPED VERTICAL 5 CURVE IN CATHODE	PCS	1	VD1
2100010	CONNECTION CORDS	Φ0.6 SHAPED 5mm	PCS	1	JP1
1562715	PCB	D333-1	PCS	1	
5070678	SELF-SEALED PLASTIC BAG (WITH HOLE)	120×260×0.05 PE	PCS	1	
2140139	POWER CONNECTING CORD	2P2.5m WITH Φ4.0 DC SOCKET	PCS	1	P+,P-
5232167	INSULATION TUBE	Φ2 WHITE	METRE	0.024	
3031156	TOP COVER OF CAR ADAPTOR BOX	AK008 BLACK	PCS	1	
3040843	BOTTOM COVER OF CAR ADAPTOR BOX	AK008 BLACK	PCS	1	
3870754	SPACER	AK008	PCS	1	
3870755	TOUCH HEAD	AK008	PCS	1	
3630186	SHRAPNEL	AK008	PCS	2	
3810034	SPRING	AK008	PCS	1	
3870756	FUSE HOLDER	AK008	PCS	1	
3060299	TOUCH HEAD COVER	AK008 BLACK	PCS	1	
2110002	CORD	24# 30mm RED	PCS	2	
2110004	CORD	24# 40mm BLACK	PCS	1	
2300018	FUSE	T3.15AL 250V (VDE/UL)	PCS	1	
5232168	DUST-PROOF NET	AK008 BLACK	PCS	4	

5. BATTERY BOX

MATERIAL CODE	MATERIAL NAME	SPECIFICATIONS	UNIT	QUANTITY	LOCATION
3029726	TOP COVER OF BATTERY BOX	DPX-I80S(ALF) SILVERY [1389]	PCS	1	
3029777	BOTTOM COVER OF BATTERY BOX	DPX-I80S(ALF) SILVERY WHITE	PCS	1	
5232318	SOFT SPONGE SPACER	150×40×4 SINGLE-FACED SOFT	PCS	2	2PCS FOR BATTERY CASE TOP COVER
3025617	GLIDE PIECE OF BATTERY BOX	DL333	PCS	1	
3025618	BUTTON OF BATTERY BOX	DL333	PCS	1	
3029776	KEY OF BATTERY BOX	DPX-I70(ALF) SILVERY WHITE	PCS	1	

3810023	SPRING OF BATTERY BOX GLIDE PIECE	DL333	PCS	2	
3810024	SPRING OF BATTERY BOX BUTTO	DL333	PCS	1	
5232022	FOOT SPACER	φ10×1 RUBBER (3M)	PCS	4	
4000481	TAPPING SCREW	CB 1.7×6H NICKEL	PCS	3	1PC FOR PCB AND BATTERY CASE BOTTOM COVER , 2PCS FOR BATTERY ADAPTOR AND BATTERY CASE BOTTOM COVER
4000522	TAPPING SCREW	CB 2×6H WHITE NICKEL	PCS	2	2PCS FOR BATTERY GLIDE PIECE AND BATTERY BUTTON
4000363	TAPPING SCREW	CB 2.6×6H NICKEL	PCS	8	8PCS FOR COVER
1510046	RECHARGEABLE BATTERY	3600mAH 7.2V Li-ion168×48×5	SUIT	1	
5154638	RECHARGEABLE BATTERY LABE	DPX-180S(ALF)	PCS	1	
5445436	PCB	B383-2 DL383D SAMPLE UNIT	PCS	1	

6. REMOTE CONTROLLER

MATERIAL CODE	MATERIAL NAME	SPECIFICATIONS	UNIT	QUANTITY	LOCATION
0310048	SMD CAPACITOR	50V 151 ±5% NPO 0603	PCS	2	C802,C803
0630009	EMISSION TUBE	TSAL4400	PCS	1	LED801
0630010	EMISSION TUBE	LTE-4206	PCS	1	LED801
0700007	SMD DIODE	1N4148	PCS	3	D801,D804,D805
0700001	SMD DIODE	LS4148	PCS	3	D801,D804,D805
0700002	SMD DIODE	LL4148	PCS	3	D801,D804,D805
0780130	SMD TRIODE	STC3265	PCS	1	Q801
0880186	IC	HT6222 SOP	PCS	1	U801
0880220	IC	PT2222 SOP	PCS	1	U801
0970003	CERAMIC RESONATOR	455E	PCS	1	X801
1631964	PCB	8917-2	PCS	1	
3030522	FRONT PANEL OF REMOTE CONTROLLER	RC017 GREY WHITE	PCS	1	
3040436	REAR PANEL OF REMOTE CONTROLLER	RC017 GREY WHITE	PCS	1	
3050356	BATTERY CASE DOOR OF REMOTE CONTROLLER	RC017 GREY WHITE	PCS	1	
3630135	ANODE SHRAPNEL OF REMOTE CONTROLLER	RC017	PCS	1	
3630136	CATHODE SHRAPNEL OF REMOTE CONTROLLER	RC017	PCS	1	
4000291	SELF-TAPPING SCREW	BB2×5 NICKEL	PCS	4	
4630557	REMOTE CONTROLLER CONDUCT GLUE	DVP-307	PCS	1	
5070004	PLASTIC GLUE	75×200	PCS	1	
5152319	REAR PANEL LABEL	RC017R	PCS	1	
5154639	REMOTE CONTROLLER FRONT PANEL	DPX-180S(ALF)	PCS	1	

7. DECODE BOARD

MATERIAL CODE	MATERIAL NAME	SPECIFICATIONS	UNIT	QUANTITY	LOCATION
0090001	SMD RESISTOR	1/16W 0Ω ±5% 0603	PCS	21	R140,R226,R227,R230,R231, R249,R302~R307,R364,R441, R443,R448,R449,R450,R238, R464,R362
0090272	SMD RESISTOR	1/16W1Ω±5% 0603	PCS	8	R116~R122,L302
0090106	SMD RESISTOR	1/16W 4.7Ω ±5% 0603	PCS	2	R111,R112
0090314	SMD RESISTOR	1/16W 5.1Ω ±5% 0603	PCS	2	R415,R416
0090599	SMD RESISTOR	1/16W 6.2Ω±5% 0603	PCS	2	R445,R446
0090003	SMD RESISTOR	1/16W 10Ω ±5% 0603	PCS	1	R113
0090005	SMD RESISTOR	1/16W 33Ω ±5% 0603	PCS	12	R143,R217~R219,R223,R224, R252~R254,R346,R452,R453
0090016	SMD RESISTOR	1/16W 1.5K ±5% 0603	PCS	1	R456
0090230	SMD RESISTOR	1/16W 47Ω ±5% 0603	PCS	2	R126,R127
0090006	SMD RESISTOR	1/16W 75Ω ±5% 0603	PCS	5	R351,R355,R356,R350,R352
0090181	SMD RESISTOR	1/16W 100Ω ±5% 0603	PCS	4	R114,R413,R414,R457
0090232	SMD RESISTOR	1/16W 150Ω ±5% 0603	PCS	1	R345
0090009	SMD RESISTOR	1/16W 330Ω ±5% 0603	PCS	4	R318,R328,R2138,R2139
0090012	SMD RESISTOR	1/16W 560Ω ±5% 0603	PCS	4	R319,R327,R365,R366
0090249	SMD RESISTOR	1/16W 510Ω ±5% 0603	PCS	1	R236

0090014	SMD RESISTOR	1/16W 1K ±5% 0603	PCS	27	R109,R110,R214,R215,R329~R333,R336~R339,R341~R343,R411,R412,R423~R425,R2137,R2141,R2143,R136,R2145,R2142
0090236	SMD RESISTOR	1/16W 1.8K ±5% 0603	PCS	1	R426
0090019	SMD RESISTOR	1/16W 4.7K ±5% 0603	PCS	10	R133,R134,R245,R246,R247,R251,R314,R315,R324,R325
0090020	SMD RESISTOR	1/16W 5.1K ±5% 0603	PCS	4	R409,R410,R312,R313
0090021	SMD RESISTOR	1/16W 6.8K ±5% 0603	PCS	2	R310,R311
0090023	SMD RESISTOR	1/16W 10K ±5% 0603	PCS	34	R103,R104,R106,R107,R141,R220~R222,R240~R242,R255,R323,R347,R418~R420,R430~R435,R438,R439,R2134~R2136,R2144,R348,R349,R461,R463,R467
0090187	SMD RESISTOR	1/16W 12K ±5% 0603	PCS	2	R427,R428
0090024	SMD RESISTOR	1/16W 15K ±5% 0603	PCS	4	R201,R202,R308,R309
0090188	SMD RESISTOR	1/16W 18K ±5% 0603	PCS	2	R243,R137
0090025	SMD RESISTOR	1/16W 20K ±5% 0603	PCS	6	R123,R124,R244,R429,R316,R317
0090255	SMD RESISTOR	1/16W24K±5% 0603	PCS	1	R135
0090481	PRECISION SMD RESISTOR	1/16W 30K±1% 0603	PCS	1	R417
0090028	SMD RESISTOR	1/16W 33K ±5% 0603	PCS	6	R359,R360,R401,R402,R454,R455
0090191	SMD RESISTOR	1/16W 39K ±5% 0603	PCS	1	R326
0090029	SMD RESISTOR	1/16W 47K ±5% 0603	PCS	9	R138,R139,R322,R403~R408
0090192	SMD RESISTOR	1/16W 51K ±5% 0603	PCS	1	R458
0090030	SMD RESISTOR	1/16W 56K ±5% 0603	PCS	2	R357,R358
0090193	SMD RESISTOR	1/16W 82K ±5% 0603	PCS	1	R340
0090034	SMD RESISTOR	1/16W 100K ±5% 0603	PCS	8	R101,R102,R203,R204,R276,R320,R321,R460
0090109	SMD RESISTOR	1/16W 1MΩ ±5% 0603	PCS	1	R466
0090212	SMD RESISTOR	1/16W 750K ±5% 0603	PCS	1	R216
0100019	SMD RESISTOR NETWORKS	1/16W33Ω ±5% 8P	PCS	2	RN201,RN301
0310549	SMD CERAMIC CAPACITOR	25V 106+80%-20% 1210	PCS	29	TC106,TC201,TC202,TC207~TC210,TC302~TC310,TC316~TC320,TC403,TC407,TC408,TC421~TC423,TC417,TC418
0310376	SMD TANTIUM CAPACITOR	NRS10V47U±20%3528(B2)	PCS	24	C101,C102,C345,TC101~TC105,TC107,TC203~TC206,TC248,TC301,TC312,TC327,TC328,TC406,TC412~TC416
0310374	SMD TANTIUM CAPACITOR	16V47UF±20% 6032(C)	PCS	3	TC315,TC401,TC424
0310375	SMD TANTIUM CAPACITOR	16V100UF±20% 7343(D)	PCS	4	TC321,TC322,TC404,TC409
0310646	SMD CAPACITOR	25V 15P ±5% NPO 0603	PCS	4	C265~C268
0310647	SMD CAPACITOR	25V 20P ±5% NPO 0603	PCS	4	C258,C342~C344
0310190	SMD CAPACITOR	50V 27P ±5% NPO 0603	PCS	6	C332,C359,C360,C443,C367,C368
0310044	SMD CAPACITOR	50V 33P ±5% NPO 0603	PCS	2	C263,C264
0310045	SMD CAPACITOR	50V 47P ±5% NPO 0603	PCS	1	C120
0310047	SMD CAPACITOR	50V 101 ±5% NPO 0603	PCS	7	C319,C320,C355~C358,C445
0310048	SMD CAPACITOR	50V 151 ±5% NPO 0603	PCS	2	C123,C124
0310645	SMD CAPACITOR	25V 221 ±5% NPO 0603	PCS	2	C440,C441
0310050	SMD CAPACITOR	50V 271 ±5% NPO 0603	PCS	3	C333~C335
0310051	SMD CAPACITOR	50V 331 ±5% NPO 0603	PCS	5	C274,C275,C336~C338
0310648	SMD CAPACITOR	25V 471 ±5% NPO 0603	PCS	1	C442
0310649	SMD CAPACITOR	25V 102 ±5% NPO 0603	PCS	11	C257,C262,C317,C318,C321,C322,C414~C417,C419
0310650	SMD CAPACITOR	25V 122 ±5% NPO 0603	PCS	2	C315,C316
0310651	SMD CAPACITOR	25V 152 ±5% NPO 0603	PCS	1	C276
0310069	SMD CAPACITOR	50V 272 ±10% 0603	PCS	1	C327
0310652	SMD CAPACITOR	25V 472 ±5% NPO 0603	PCS	1	C444
0310072	SMD CAPACITOR	50V 103 ±10% 0603	PCS	2	C122,C273
0310201	SMD CAPACITOR	50V 153 ±10% 0603	PCS	1	C272
0310055	SMD CAPACITOR	16V 333 ±10% 0603	PCS	1	C256
0310056	SMD CAPACITOR	16V 473 ±10% 0603	PCS	2	C259,C260

0310594	SMD CAPACITOR	25V 104 ±10% 0603	PCS	92	C103~C107,C109,C110,C112~C117,C125,C126,C201~C215,C217~C248,C269,C298,C301,C306~C309,C311,C346,C348~C350,C352~C354,C420,C424,C428,C429,C433~C436,C438,C439,C361,C362,C363,C351,C366
0310112	SMD CAPACITOR	16V 224 ±10% 0603	PCS	2	C412,C413
0310542	SMD CAPACITOR	16V 474±10% 0603	PCS	9	C261,C339,C340,C406~C411
0310234	SMD CAPACITOR	16V 105 +80%-20% 0603	PCS	18	C418,C249~C255,TC323~TC326,C401~C405,C341
0390096	SMD INDUCTOR	1.8UH ±10% 1608	PCS	3	L328~L330
0390328	SMD MAGNETIC CORE INDUCTOR	2.2UH±30% CDH5B18	PCS	1	L426
0390241	SMD MAGNETIC CORE INDUCTOR	10uH±20%CDRH5D18	PCS	2	L404,L427
0390336	SMD MAGNETIC CORE INDUCTOR	10UH±20% CDH10D45	PCS	1	L403
0390302	SMD MAGNETIC BEADS	MGHB1608S102	PCS	31	L110,L119,L202,L204~L211,L213,L216,L242,L244,L301,L304~L312,L315~L317,L326,L327,L331
0390259	SMD MAGNETIC BEADS	FCM2012-120T2A	PCS	18	L107,L109,L120,L318,L325,L401,L402,L406,L409,L411~L413,L425,L418,L419,L428,L429,L408
0700007	SMD DIODE	1N4148	PCS	7	VD101,VD208,VD301,VD302,VD303,VD307,VD308
0700001	SMD DIODE	LS4148	PCS	7	VD101,VD208,VD301,VD302,VD303,VD307,VD308
0700002	SMD DIODE	LL4148	PCS	7	VD101,VD208,VD301,VD302,VD303,VD307,VD308
0700056	SMD DUAL-DIODE	MMBD4148SE SOT-23	PCS	3	VD304~VD306
0700063	SMD DUAL-DIODE	MMBD4148CA SOT-23	PCS	1	VD201
0680027	SMD SCHOTTKY DIODE	SS34	PCS	3	VD401,D401,D402
0680028	SMD SCHOTTKY DIODE	MBRS340	PCS	1	VD402
0680024	SMD SCHOTTKY DIODE	1N5819 (HOME MADE)	PCS	1	VD402
0680042	SMD SCHOTTKY DIODE	BAT54S SOT-23	PCS	4	VD403~VD406
0700139	SMD VOLTAGE REGULATOR DIODE	17V 1/2W MINIMELF	PCS	1	ZD401
0700140	SMD VOLTAGE REGULATOR DIODE	13V 1/2W MINIMELF	PCS	1	ZD402
0780085	SMD TRIODE	8050D	PCS	6	Q406,V206,V218,V306,Q408,V219
0780129	SMD TRIODE	8550D	PCS	5	Q404,V210,V303~V305
0780197	SMD TRIODE	C1815	PCS	6	V301,V302,V308,V309,V310,V311
0780041	SMD TRIODE	3906	PCS	2	V403,V404
0780193	SMD TRIODE	2SK3018	PCS	2	V102,V103
0780115	SMD TRIODE	2SB1132	PCS	2	V104,V105
0780040	SMD TRIODE	3904	PCS	3	V101,V401,V402
0790021	FIELD EFFECT TUBE	IRF7416 SOP	PCS	2	Q401,Q402
0790041	FIELD EFFECT TUBE	SI2305DS SOT-23	PCS	2	Q403,Q407
1990027	3-IN-1 CARD HOLDER	SD/MS/MMC 23芯 H=4.2 TOP	PCS	1	JK402
0880185	IC	NJM4558M SOP	PCS	1	U305
0880562	IC	4580 SOP	PCS	1	U305
0880361	IC	4558 SOP	PCS	1	U305
0881415	IC	HY57V641620HGT-7 TSOP	PCS	1	U202
0881189	IC	MT48LC4M16A2-7 SOP	PCS	1	U202
0881937	IC	TPA0152 TSSOP24	PCS	1	U209
0882022	IC	CS4340A SOP	PCS	1	U304
0881031	IC	24C02N SOP	PCS	1	U101
0881855	IC	XC602P502PR SOT-89	PCS	1	U303
0881631	IC	XC6201P502PR SOT-89	PCS	1	U303
0881914	IC	RT9701CB SOT25	PCS	4	U306,U402,U403,U406
0881892	IC	XC6202P802PR SOT-89	PCS	1	U301
0881513	IC	BA6849FM HSOP	PCS	1	U103
0881682	IC	BA6849FP HSOP	PCS	1	U103
0881994	IC	MT1389FE QFP	PCS	1	U201
0881405	IC	BA5954FM HSOP	PCS	1	U104
0882269	IC	AAT1343T2 TSSOP	PCS	1	U401
0882268	IC	AAT1102M MSOP	PCS	1	U405
0882105	IC	LM393 SO8	PCS	1	U105
0881182	IC	LM1117MP-ADJ SOT-223	PCS	1	U404

0882202	IC	AU9362A21-MCL QFP	PCS	1	U501
2360016	IR SENSOR	HS0038B3V	PCS	1	U102
0960020	CRYSTAL OSCILLATOR	27.00MHz 49-S	PCS	1	X201
0960019	CRYSTAL OSCILLATOR	12.00MHz 49-S	PCS	1	X202
1631854	PCB	2383D-1	PCS	1	
1940227	SOCKET	3P 1.25mm SMD	PCS	1	XS205
1940150	SOCKET	4P 1.0mm SMD	PCS	2	XS102,XS302
1940205	SOCKET	16P 1.0mm SMD	PCS	1	XS203
1940208	CABLE SOCKET	30P 0.5mm SMD WITH CLASP	PCS	1	XS101
1940229	CABLE SOCKET	15P 0.5mm SMD WITH CLASP	PCS	1	XS104
1350062	TESTING SWITCH	DS-24	PCS	1	SW201
0620067	DUAL-COLOR RADIATION DIODE	2RG59PC RED AND GREEN 2×4.5×4	PCS	1	LED201
0620086	DUAL-COLOR RADIATION DIODE	2.5RG59HW-A×5 RED AND GREEN	PCS	1	LED201
1870021	POWER SOCKET	DC-023	PCS	1	JK501
1090049	ELECTRO-OPTICAL TRANSFORM	GP1FD310TP	PCS	1	JK203
1910101	AV SOCKET	PJ-327 BLACK	PCS	3	JK204,JK306,JK308
1910104	AV SOCKET	PJ-327 YELLOW	PCS	1	JK208
1910105	AV SOCKET	PJ-327 WHITE	PCS	1	JK207
1980051	HEADPHONE SOCKET	ST-202A-050-100 YELLOW	PCS	1	JK206