

SAMSUNG


WASHING MACHINE

S803JGE3/YLW

S803JGE3U/YLW

SERVICE Manual

WASHING MACHINE



CONTENTS

 Caution for the safety during servicing

1. SPECIFICATIONS
2. SAFETY DEVICES
3. OVERVIEW OF THE WASHING MACHINE
4. OVERVIEW OF THE CONTROL PANEL
5. MAIN FUNCTION
6. TECHNICAL POINT
7. GENERAL ERROR FUNCTION
8. TROUBLE DIAGNOSIS
9. TEST MODE
10. DESIGNATION OF MAIN COMPONENTS
11. PCB SCHEMATIC DIAGRAM
- 11-1. PCB CIRCUIT DIAGRAM
12. SETTING UP A WASH MACHINE
13. ASSEMBLE AND DISASSEMBLE
14. TOOLS FOR DISASSEMBLY AND ASSEMBLY
15. EXPLODED VIEW AND PARTS LIST



Caution for the safety during servicing

1. Do not allow the customer to repair the product.

⚠ The person may be injured or the product life may be shortened.

2. Execute A/S after unplugging the power supply unit.

⚠ Be care of the electric shock.

3. Do not plug several plugs in the same outlet.

⚠ It may cause the fire due to overheat.

4. Check the damage, pressing or burning of the power plug or outlet.

⚠ Replace it promptly if it has problem. (may cause the electric shock or fire)

5. Do not clean the main body with the water.

⚠ It may cause the electric shock and fire and shorten the product life.

6. The wiring of the harness shall be free from the moisture and tightened during serving.

⚠ It shall not be deviated by certain impact.

7. Remove any dust or filth on the housing section,wiring section,connection section during servicing.

⚠ Protect the cause of the fire such as the tracking,and etc.

8. Check any mark of the moisture on the electrical parts, harness section and etc.

⚠ Replace the parts or remove the moisture.

9. Check the assembly status of the parts after servicing.

⚠ Maintain the status before servicing.

10. Pull out the power cord with holding the plug.

⚠ Be care of the electric shock and fire when the cord is damaged.

11. Unplug the power plug from the outlet when the wash machine is not used.

⚠ Be care of the electric shock and fire due to the strike of the lightening.

12. Do not use or store the spray or flammable materials(including gasoline,alcohol and etc.) around the wash machine.

⚠ Be care of the explosion or fire due to the electric spark.

13. Do not put the bowl of water or wet laundry on the wash machine.

⚠ If the water is penetrated to the wash machine, this may cause the electric shock or fire.

14. Do not install the wash machine in the place where the snow or rain falls.

⚠ It may cause the electric shock and fire and shorten the product life.

15. Do not push the control buttons with the awl,pin, or sharp materials.

⚠ It may the electric shock and trouble.

16. Check the wash machine is leveled horizontally and installed properly on the floor.

⚠ The vibration may shorten the product life.

17. Joint the wire by the connector correctly.

⚠ When the wire is jointed by the tape, this may cause the fire due to the tracking.

18. When the wash machine is to be laid for the service, put the pad on the floor and lay the product at side slowly.

⚠ If the wash machine is laid front, the relay may be damaged by the tub.

19. When the wash-heater is replaced, check it is inserted in the bracket-heater and screw the nut.

⚠ If the wash is not inserted in the bracket-heater properly, this may cause the noise and leakage since it is contacted to the drum.

1. Specifications

WASH TYPE	FRONT LOADING TYPE			
DIMENSION	GROSS	W 680mm X D 470mm X H 892mm		
	NET	W 598mm X D 340mm X H 844mm		
WATER PRESSURE	50 kPa ~ 800 kPa			
WEIGHT	GROSS	58 kg		
	NET	55 kg		
WASH and SPIN CAPACITY	3.5 kg (DRY LAUNDRY)			
POWER CONSUMPTION	WASHING		220 V	70 W
			240 V	70 W
	WASHING and HEATING		220 V	1800
			240 V	2100
	SPIN	MODEL	S803J	
		220-240V	200 W	
	PUMPING		34 W	
WATER CONSUMPTION	43 ℓ (STANDARD COURSE)			
SPIN REVOLUTION	MODEL	S803J		
	rpm	800		

2. Safety Devices

※ We adapt 5 safety devices for users to use this wash machine safely.

1) Balancing device (ASSY-Main PCB)

→ When the laundry is out of balance, to prevent the noises and vibrations, the unbalance detecting sensor helps the laundry laid even and continue the dehydrating process.

2) Anti-over water supply device

→ Because water supply valve is broken, once water is supplied to the 2/3 level of the door, the water supplied is drained automatically, Over -flow error (E3) is displayed on the panel

3) Temperature-regulating device(thermistor)

→ To prevent over-heating over the temperature set up, THERMISTOR senses the temperature of the machine continuously and helps the wash machine to work at the temperature given by users.



4 Overheating- controlling system

→ Under the circumstances of THERMISTOR inferiority or abnormal condition, if wash-heater is overheated, automatically, assy -thermal fuse cuts off the power supply to protect the machine to keep it safe.

5) Delicate clothing safeguard function(ASSY-Main PCB)


→ To protect the clothings which is weak to high temperature, the wash machine senses the temperature inside the washing tub. if the temperature rises over 50℃ wool washing course and Delicate washing course display abnormal water temperature on the panel , after draining the water.

3. Overview of the Washing Machine



4. Overview of the control panel

S803J



1. Detergent dispenser

2. Display panel

Displays the remaining wash cycle time and error messages.

3. Wash Button

Press the button repeatedly to cycle through the available partial wash options { Eco⁺ → Prewash → Soak Wash → Cancel → Eco⁺ }.

Note : Prewash/Eco+ is available only with Cotton, Colour, Synthetic or Delicate programs.

4. Rinse Button

Press the button repeatedly to cycle through the available partial rinse options (Water⁺ → Rinse⁺ → Water⁺+Rinse⁺ → Cancel → Water⁺).

Note : Prewash/Eco+ is available only with Cotton, Colour, Synthetic or Delicate programs.

5. Spin selection button

Press the button repeatedly to cycle through the available spin speed options.

S803J	no spin, rinse hold, 400, 600, 800 rpm
-------	--

When pressing this button during operation, you can see the selected spin speed in the display panel.

6. Temperature selection button

Press the button repeatedly to cycle through the available water temperature options (cold water, 30 °C, 40 °C, 60 °C and 95°C).

When pressing this button during washing, you can see the selected temperature in the display panel.

7. Delay Start button

Press the button repeatedly to cycle through the available delayed start options (from 1 hour to 24 hours in one hour increments).

8. Fuzzy Control dial

Turn the dial to select one of the nine available wash programs.

Baby Cotton, Cotton, Colour, Synthetic, Delicate, Wool, Quick, Rinse+Spin, Spin, Drain
--

9. Start/Pause button

Press to pause and restart programs.

10. ① (On/Off) button

Press once to turn the washing machine on, press again to turn the washing machine off. If the washing machine power is left on for longer than 10 minutes without any buttons being touched, the power automatically turns off.

5. Main function

1) Auto power S/W off function

- After power on, the auto power S/W off function automatically switches power off for you if you do not press selection button for 10 minutes
- After selecting the function, the auto power S/W off function automatically switches power off for you if you do not press start/pause button for 10 minutes
- until 5 minutes past, After finishing the last function, the auto power S/W off function automatically switches power off for you if you do not re-select the course button or manual button

2) Door open function

- If door is open during the operating, all operating is halted, and door error message will be displayed (2-digit panel displays "Ed" 4-digit panel displays "door") and error melody will coming out
- Door open error can be cleared by closing the door. the operating keeps going on

3) Rinse hold function

- If rinse hold function selected, the operating is finished , the machine do not drain the water after last rinse

4) No spin function

- If no spin function selected, the operating is finished after last rinse

5) Drain function

- Drain function is over, after pumping out the water for 2 minutes , without motor rotating

6) Pre-washing function

- Pre-washing function can be selected ,when you choice the following mode; cotton, coloreds, sythetics, delicates, baby cotton
- Water level/reverse time is the same with the selected course
- Pre-washing takes about 15 minutes

7) Rinse+ function


- This function practises rinse process once more

5. Main function

8) Power-out compensation function

- If power is out on selected process, the process before power out is stored to EEPROM, once power is back the process before power out continues.
- When power is back, washing process starts from the process at the point of the power out, rinse/drain process starts from the initial process.

POWER-OUT COMPENSATION FUNCTION PROCESS



9) Water heater Error function

- ① This function starts working, when the heater works abnormally.
(this function begins sensing the heater 2 minutes later, after the heater operating)
- ② The value of the initial thermistor(A1) is compared with that of the thermistor(A2) in 2 minutes ($Y=A2-A1$)
- For 10 minutes, the variance of temperature(Y) is less than 2°C "E5" message is displayed on the panel.
- ③ The value of the initial thermistor(A1) is compared with that of the thermistor(A2) in 11 minutes ($Y=A2-A1$)
- For 1 minute the variance of temperature(Y) increases more than 7°C (0.3V) "E6" message is displayed on the panel.
- ④ At this time heater, Error "E5 (heater do not work), E6(overheated)" is displayed and all working process off
- ⑤ The heater operating continues during heating hours, if washing hour is left over, the residual washing process keeps going without heating.

5. Main function

10) Fuzzy washing function (weight-sensing)

After finishing initial water supply, when the fall of the water level needs supplementary water supply, Sensing function perceives the weight with the supplementary water supply numbers and starts to work. Under the course of Cotton, or Coloureds, if the supplementary water supply numbers become 3 - 4 times the function is going at default condition (high water level), if 1-2 below that is going at middle level, if 0 below low water level, heating hours and rinse hours depend on the above data.

ECO PRE mode is selected, the process going on at default condition.

	Washing hours		Rinse water level
	Cotton	Coloureds	
High	Default	Default	Default
Middle	Default-12 min	Default-7min	22.80KHZ
Low	Default-25 min	Default-15min	23.30KHZ

※After sensing weight, above hours is decreased from above default hours

11) Bubble -detecting function

At the each condition of washing&dehydrating , rinse&dehydrating , hydrating, bubble -detecting function works, this function works 5times normally, if the function detects bubbles at 6 times , the bubble-detecting function stops and go on to the next process.


- The bubble-detecting function during washing & dehydrating to rinse & dehydrating

after 2 times instant dehydrating and before main dehydrating, if the water level is under 25.45KHZ, Bubble

→ Detecting function thinks there are bubbles and add the bubbles-removing rinse, needing hours are above hours and 8 min 40 sec.

→ The bubble-detecting function during single hydrating process


after 2 times instant dehydrating and before main dehydrating , if the water level is 25.45KHZ below or during main dehydrating, water level data is 23.80KHZ below Bubble-detecting function thinks there are bubbles and add the bubbles-removing rinse 1 times, needing hours are above hours and 5 min 55 sec.



5. Main function


12) Unbalance detecting & laundry balance positioning system

- ① Just before the hydrating process and just after reversal rotation for balancing laundry position, this function is carried out
- ② The initial 6 sec is the period of reversal rotation for balancing laundry position , Drum rotates 50rpm for initial 6 sec
- ③ Next 10 sec, the rotation increases the speed from 50 rpm to 90 rpm slowly
- ④ During the next 18 sec, drum rotates at the speed of 90 rpm, the sensor decides the degree of laundry unbalance with TACHO data which is attached to motor
- ⑤ If the degree of unbalanced laundry is over 6 times to default value, laundry balancing system carries out feed back process 6 times



13) R.P.M control

The rotating motor enables the magnetics(i.e generator) to generate magnetic flux in proportion to r.p.m, magnetic flux induced by coil sensor in the opposite side produces the wave like the figure below to and via rectangular wave generating circuit, the waves reaches MICOM and micom controls r.p.m with the pulse, count and cycle inputted by program.



6. Technical point

1) Motor on/off time at each course

unit:sec

Course	Washing				Rinse				Motor r.p.m
	Cw	Off	Ccw	Off	Cw	Off	Ccw	Off	
Baby cotton	5	15	5	15	5	15	5	15	45
Cotton	13	3	13	3	10	5	10	5	50
Coloureds	11	4	11	4	10	5	10	5	50
Synthetics	7	8	7	8	7	8	7	8	40
Delicates	5	10	5	10	5	10	5	10	30
Wools	2	58	2	58	2	28	2	28	25
Quick	12	3	12	3	10	5	10	5	45

※ Motor on/off time is measured in cold water, in heating time motor on/off time is 10 sec on and 5sec off in the cotton course, beside cotton course, in the other course motor on/off time is the same with that of cold water use.

2) Final dehydrating r.p.m at each course

unit:rpm

Course \ Model	S803J
Baby cotton	800
Cotton	800
Coloureds	800
Synthetics	800
Delicates	600
Wools	400
Quick	800

※ You can change the r.p.m to the above a table by use spin button under no spin situation.

3) The water supply control at each process cycle

Process cycle \ Model	S803J
Washing	Cold water 4.5L/min + cold 10L/min
Rinse	Cold water 4.5L/min + cold 10L/min
Final rinse	Cold water 4.5L/min + cold 10L/min + cold 2L/min

6. Technical point

4) The water level data at each course

unit:Khz

Course \ Water level		Default water level(khz)		Supplemetary water START(Khz)	Supplemetary water end(khz)
Baby cotton	Washing	23.50		24.00	23.70
	Rinse	22.45		24.00	23.50
Cotton	Washing	23.50		24.00	23.70
	Rinse	large	22.45	24.00	23.50
		middle	22.80		
		small	23.30		
Coloureds	Washing	23.50		24.00	23.70
	Rinse	22.45		24.00	23.50
Synthetics	Washing	23.50		24.00	23.70
	Rinse	22.45		24.00	23.50
Delicates	Washing	22.80		23.55	23.35
	Rinse	22.65		23.55	23.35
Wools	Washing	22.45		23.35	23.00
	Rinse	22.15		23.35	23.00
Quick	Washing	23.50		24.00	23.70
	Rinse	22.45		24.00	23.50

5) The other water level data

unit:Khz

The water data unter each conditon		
1st water supply (only preparation)	24.60	1st water supply level to washing tub
Overflow error	20.50	The water supplied reach 2/3 of door
Bubble detectingatwashing/rinse/dehydrating	25.45	Bubble -detecting water level
Bubble detecting rinse water level	22.00	The water level which can detect bubbles
Water level which can open door	23.80 over	It is possible to open the door
Water level which can drive heater	24.50	Safety water level of wash heater
Water level which can reset the drain	24.50	The water level can be detected after 1st draining

※ If water level is 15KHZ below or 30 KHZ above , sensor-pressur is out of order so needs changing.

7. General Error Function

When an error occurs, this function starts to keep generating error melody sounds and displays error indicators as shown in the followings per corresponding error by blinking in 0.5sec interval until the error status is completely cleared out. In this case, all the driving devices are turned off until the error is cleared out.

1. WATER SUPPLY ERROR

- Display shows E1f .
- Water Supply Error occurs when water level frequency does not show changes more than 100Hz or water is not supplied up to the water level presetting for 20 min or more at the time of initial water supply.
- The error status can be cleared by turning POWER S/W OFF and resuming the POWER ON initial status.

2. WATER DRAIN ERROR

- Display shows E2f .
- In case the water level frequency is 24.5KHz or less in the initial phase of UNB-detecting cycle.
- Water Drain error can be cleared by turning POWER S/W OFF and resuming the POWER ON initial status.

3. OVER-FLOW ERROR

- Display shows E3f .
- Over-Flow error occurs when the water level is in abnormal operation. It can be cleared by turning POWER S/W OFF. Water is drained prior to POWER S/W OFF and it is forced to be drained for 2 min if a frequency of more than 24.5 KHz is detected.

4. DOOR OPEN ERROR

- Display shows Edoorf or 'Ed'
- Door Open error can be cleared by closing the door.

5. UNBALANCE ERROR

- Display shows E4f .
- Laundry load is unbalanced; loosen any tangled laundry.
- If only one item of clothing needs washing, such as a bathrobe or jeans, the final spin result might be unsatisfactory and an E4f error message will be shown in the display window.
- Unbalance error is cleared by POWER S/W OFF and by resuming the POWER ON initial status.

6. WATER HEATER ERROR

- Display shows E5,E6f .
- In case the water temperature rises by 7°C or more in 1 min. or by 2°C less in 10 min after heating is started.
- It can be cleared by turning POWER S/W OFF.

7. ASSÍ Y PRESSURE S/W ERROR

* Generated Frequency Signal of WATER LEVEL(W/L) S/W (KHz)

Level	Low Level	High Level
Abnormal W/L Frequency	30.00 KHz	15.00 KHz

- If the same signal as the above table is detected for more than 5 seconds, it is a PRESSURE S/W Error.
- When the error occurs, water drain pump will operate for 3 min. and then turn off the water drain pump. Then the display shows E7f indicating a pressure s/w error indicator.

8. ABNORMAL WATER TEMPERATURE ERROR

Course	Water Temp
Delicate	50°C or more
Wool	50°C or more

- In case the water temperature is 50°C or more in Delicate and Wool course.
- At the time of initial water supply, if the water temperature is not appropriate, water starts to be drained and it is forced to be drained for 2 min when the abnormal frequency of 24.5KHz is detected.
- Display shows E8f .
- This error can be cleared by POWER S/W OFF.

9. WATER LEAKAGE ERROR (E9)

- Water Leakage error occurs when water is drained naturally after washing program starts.

7. General Error Function

10. Tacho Error

- This error occurs in case motor thaco is out of order or tacho signals inputted are fewer than 2
- "EA" displayed
- This error can be cleared by power s/w off

11. Motor Triac short Error

- This error occurs in case over 300 per 1 sec tacho signals are inputted power S/w should be off.
- "Eb" displayed.
- This error can be cleared by power s/w off

12. Thermistor error

- This error occurs, when Thermistor circuit is abnormal or the detected electrical volt is 0.2v below or 4.5v over
- "Ec" displayed
- This error can be cleared by power s/w off


8. Trouble Diagnosis

- As the micom wash machine is configured of the complicate structure, there might be the service call. Below information is prepared for exact trouble diagnosis and suitable repair guide.

Caution for the Repair and Replacement

Please follow below instruction for the trouble diagnosis and parts replacement.

- 1) As some electronic components are damaged by the charged static electricity from the resin part of wash machine or the human body, prepare the human body earth or remove the potential difference of the human body and wash machine by contacting the power supply plug when the work contacting to PCB is executed.





- 2) Since AC220~240V is applied to the triac T1 and T2 on P.C.B, the electric shock may occur by touching and be careful that the strong and weak electricity are mixed.
- 3) As the P.C.B assembly is designed for no trouble, do not replace the P.C.B assembly by the wrong diagnosis and follow the procedure of the trouble diagnosis when the micom is not operated normally.

8-1. Trouble Diagnosis



No	Item	Cause and treatment
1	The power is not supplied	- Is the PCB connector connected well? - Is the voltage normal? - Is the power supply plug connected well? - Is the noise filter connected well? - Is the secondary output of the power supply transformation normal? - Is the fuse disconnected? (option) ▮ If above points are not found, the PCB assembly is out of order. Replace it.
2	The water is not supplied.	- Is the knob open? - Did you push START/PAUSE button after selecting the course? - Is the water supply valve connected well? - Is the winding of the water supply valve continuous? - Is the connection and operation of the pressure switch normal? ▮ If above points are not found, the PCB assembly is out of order. Replace it.
3	The wash does not start though the water supply is stopped.	- Is the connection and operation of the pressure switch normal? - Is the pressure switch hose damaged so that the air is leaked? - Is the pressure switch hose bent? - Check the operation of the water level switch. ▮ If above points are not found, the PCB assembly is out of order. Replace it.
4	The drum does not rotate during washing.	- Is the belt connected well? - Is the winding of the motor continuous? (Rotor winding, stator winding, generator) - Is the motor protector normal? ▮ If above points are not found, the PCB assembly is out of order. Replace it.
5	The drum rotates by one direction during washing. (The drum rotates to one direction for SPIN.)	- The PCB assembly is out of order. Replace it. (Inversion relay open trouble)
6	Drainage problem.	- Is the drainage hose bent? - Is the winding of the drainage pump continuous? - Is the drain filter clogged by the waste? ▮ If above points are not found, the PCB assembly is out of order. Replace it.
7	Dehydration problem.	- The unbalance is detected. - Put in the laundry uniformly and start again.
8	Abnormal noise during SPIN.	- Is the pulley nut loosen? - Is the transport safety device removed? - Is the product installed on the level and stable place? (Little noise may be generated during the high-speed SPIN.)
9	Leak breaker or current/leak breaker is down during washing.	<When the leak breaker and current breaker is installed separately> - When the leak breaker is down, check and make the earth of the outlet. - When the current is down, the current is leaked. <Is the breaker down when the leak/current breaker is combined?> - Check the rated capacity of the current and leak breaker. The current breaker may be down due to the lack of the current when the wash machine and other apparatus are used. In this case, execute the cold water wash to check whether the current capacity is lack.
10	The heating is not executed.	- Is the wash heater terminal unplugged? - Is the wash heater normal? ▮ If above points are not found, the PCB assembly is out of order. Replace it.

8-2 . Problem Checking And Method Of PCB



8-2-1 The Part Of Power Source




8-2-2. Reset Part




8-2-3. Interrupt Part



8-2-4. Checking The Part Of An Oscillator





8-2-5. Check The Part Of Buzzer



8-2-6. Driving Part Checking



- ◆ Confirm The Output Of DC5V, When The Every Part Of Micom Number Check, According To The Some Problem Condition

ex) When The Drain Is Not Operating But Pump Motor Is Operating, Check The 5Voltage Of Micom





※ Check The Micom 18th In The Above Method When The Cold Water Is Bad


8-2-7. Confirm The Driving Part Of Motor



8-2-8. Checking The Tacho Part



9. Test Mode



1. Driving Compartment Test Mode

- A. Hold down 1 and 2 keys simultaneously and then press POWER S/W 4 on.
(Whole lamps turn on and display show t1 after 3 Seconds.)
- B. The driving compartment can be tested when you press 3 key right after entering into the initial stage of the TEST MODE.

i Driving Compartment Test


Pre-wash VALVE ON(0.3sec) → OFF(0.3sec) → COLD VALVE ON(0.3sec) → [OFF(0.3sec) → HOT VALVE ON (0.3sec) : **OPTION**] → OFF(0.3sec) → Rinse VALVE ON(0.3sec) → OFF(0.3sec) → Pump MOTOR ON(0.3sec) → OFF(0.3sec) → MOTOR Left (0.5sec) → OFF(0.5 sec) → MOTOR Right (0.5sec) → OFF(0.3sec) → HEATER RELAY ON(0.3sec) → OFF(0.3sec) → DOOR OPEN
(Function continues when door is closed)

2. THERMISTOR TEST MODE

- A. Hold down 1 and 2 keys simultaneously and then press POWER S/W 4 on.
(Whole lamps turn on and display show t1 after 3 Seconds.)
- B. Press the 1 key and display shows t2
- C. Press the 3 key and display shows the inside temperature of tub.


10. Designation of Main Components

10-1 Normal / Reverse Revolution of Motor and R. P. M. Control




(± 7%)	STATOR(5.1)	STATOR(5.1)	ROTOR(8.9)	TACHO(3.4)	PROTECTOR(6.7)	"H"(mm)	Code-No.	Remark
Resistance value	2.07Ω	0.90Ω	2.35Ω	42.7Ω	0	45	DC31-00002C	
	—	1.592Ω	2.094Ω	38.8Ω	0	39	DC31-00002C	
Rated value	220~240V/50Hz							

10-2 Door safety Device



10-3 Heater

- 1) Capacity : AC 230V/1900W
- 2) Location : Bottom of TUB
- 3) Function : Raise the water temperature supplied at the wash process.
- 4) Resistance value : 23~29
- 5) Thermal Fuse : 128℃



10-4 Detergent tub and water supply value

A Detergent tub is composed of housing and 3 drawers . supplied water flows into the 3 drawer-detergent tub by way of classifier at each washing process.

three open drainage way whith detergent and supplied water by way of connector located under the housing flows into washing tub.

the water supply valve is composed of a hot water valve(1 way) and a cold water valve(3way) and water flow per min in the valve is below.

	Hot water valve(1 way)	Cold water valve(3 way)		
		V1	V2	V3
water flow(L/min)	5L	2 L	10L	4.5L
resistance value	4.3kΩ	4.2kΩ	4.2kΩ	4.2kΩ
power consumption	AC 220v ~ 240V 50/60Hz			
usable water pressure	0.5 ~ 8 kg/cm ²			


10-5 Shock absorber and buffer spring

This wash machine is equipped with 2 Shock absorbers with same capacity and with 2 buffer springs. 2 Shock absorber are placed under the tub and outside case , 4 buffer springs are placed on the right and left of the upper side of outside case.


Shock absorber function: during wash, dehydration absorb the shock.

buffer spring: buffering the vibration

device	capacity of Shock absorber
Shock absorber	8±2kg




10-6 ASSY-TUB BACK



(unit : mm)

TYPE	INNER-BEARING(A)	OUT-BEARING(B)	OIL-SEAL(C)	Assy-Housing Bearing(D)	Assy-Tub Back	REMARK
I	□20	□17	□24.3	DC97-02133A	DC97-02137A	

10-7 ASSY- DRUM




(unit : mm)


TYPE	(A)	(B)	(C)	CODE-NO.	REMARK
I	□20	□17	□25	DC97-02099A	Lifter type

10-8 ASSY-PUMP DRAIN

- 1) Capacity : AC 230V 34W
- 2) Location : Front bottom(R)
- 3) Resistance : 15Ω ~ 18Ω




11. PCB Schematic Diagram



11-1. PCB CIRCUIT DIAGRAM

```
/disc/model/mod2/sw-p12/pv2
```



11-1. ASSY-PCB Part List

LOCATION NO.	CODE NO.	DESCRIPTION	SPECIFICATION	Q'TY	REMARK
WDD01	1401-001007	THYRISTOR-TRIAC	10A,800V,20uA,300V/uS,TO-220AB	1	TRIAC1
WDD01	1401-001024	THYRISTOR-TRIAC	2A,800V,20UA,300V/US,TO-220F	1	TRIAC2
WDD01	1401-001024	THYRISTOR-TRIAC	2A,800V,20UA,300V/US,TO-220F	1	TRIAC3
WDD01	1401-001024	THYRISTOR-TRIAC	2A,800V,20UA,300V/US,TO-220F	1	TRIAC4
WDD01	1401-001024	THYRISTOR-TRIAC	2A,800V,20UA,300V/US,TO-220F	1	TRIAC5
WDD01	1401-001024	THYRISTOR-TRIAC	2A,800V,20UA,300V/US,TO-220F	1	TRIAC7
WDD02	0402-001023	DIODE-BRIDGE	RBV1506,600V,15A,SIP-4	1	B/D
WDD03	3501-001180	RELAY-MINIATURE	12VDC,400mW,-,2FormC,7mS,3mS	1	RELAY3
WDD04	3501-001156	RELAY-POWER	12VDC,0.53W,16000MA,1FORMA,20MS,10MS	1	RELAY1
WDD04	3501-001156	RELAY-POWER	12VDC,0.53W,16000MA,1FORMA,20MS,10MS	1	RELAY2
WDD05	0402-000137	DIODE-RECTIFIER	1N4007,1000V,1A,DO-41,TP	1	D14
WDD05	0402-000137	DIODE-RECTIFIER	1N4007,1000V,1A,DO-41,TP	6	D15~D19
WDD06	0504-000130	TR-DIGITAL	KSR1105TF,NPN,200MW,4.7K/10K,SOT-23,TP	1	TR3
WDD06	0504-000130	TR-DIGITAL	KSR1105TF,NPN,200MW,4.7K/10K,SOT-23,TP	1	TR4
WDD06	0504-000159	TR-DIGITAL	KSR2105,PNP,200MW,4.7K/10K,SOT-23,TP	1	TR1
WDD06	0504-000159	TR-DIGITAL	KSR2105,PNP,200MW,4.7K/10K,SOT-23,TP	1	TR2
WDD07	DE13-20016A	IC-VOLT REGU	KA7805A,TO-220AB,1A,0/125C,-,-	1	TR7
WDD08	0501-000465	TR-SMALL SIGNAL	MMBT3904,NPN,350mW,SOT-23,TP,100-300	2	TR5,TR6
WDD09	1202-000141	IC-VOLTAGE COMP.	7033,SOT-89,3P,-,SINGLE,0V,-,P	1	IC4
WDD10	2802-000188	RESONATOR-CERAMIC	8MHz,0.5%,TP,10.0x5.0x8.0mm	1	RESO
WDD11	DE13-20017A	IC-DRIVE	KID65003AP,DIP,16P,STICK,TR-AR	3	IC3,IC5,IC6
WDD12	1103-001203	IC-EEPROM	524C20D21,128x8Bit,DIP,8P,300MIL,-,2.5V,-,PL	1	IC2
WDD13	DE30-20016A	BUZZER	CBE2220BA,STICK,-,-,-,-,-,-	1	BZ
WDD14	3404-000282	SWITCH-TACT	12Vdc,50mA,120gf,6x6x5mm,SPST	1	SW2
WDD14	3404-000282	SWITCH-TACT	12Vdc,50mA,120gf,6x6x5mm,SPST	1	SW3
WDD14	3404-000282	SWITCH-TACT	12Vdc,50mA,120gf,6x6x5mm,SPST	1	SW4
WDD14	3404-000282	SWITCH-TACT	12Vdc,50mA,120gf,6x6x5mm,SPST	1	SW5
WDD14	3404-000282	SWITCH-TACT	12Vdc,50mA,120gf,6x6x5mm,SPST	1	SW7
WDD14	3404-000282	SWITCH-TACT	12Vdc,50mA,120gf,6x6x5mm,SPST	1	SW8
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L10
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L11
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L14
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L15
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L21
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L22
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L23
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L24
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L25
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L29
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L30
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L31
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L32
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L33
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L34
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L35
WDD15	DE07-20040A	LED LAMP	SLH-34VC70F,RED,T,PI5,-,-,-,-	1	L36
WDD16	DE07-00011A	LED DISPLAY	A4232GM-0,23.7*18.7*17.2,GRN,2dig,14seg,-,-	1	DISP
WDD18	DE34-20071A	SWITCH-ROTARY	DC10V,1MA,SH,PA-1005A-003-000,	1	E/SW

12. Setting up a wash machine.



12-1 Remove the safety device for carriage

- 1) Remove 5 safety device volts with a enclosed wrench for safety device remove
- 2) Plug the 5 holes with 5 caps after removing the 5 safety device volts.

* Take care of 5 safety device volts and a wrench , you need these when you move wash machine safely.

Caution

You must remove safety device before use , if not, you have much vibration or much load can by impacted on the machine.



12-2 Install the wash machine on the leveled place.

With the water level adjustment device, adjust the 4 adjustment legs to install the machine leveled on the right, left, front and rear side. machine's install condition and size is following.

12-2-1 Initial assembled condition (ass'y cover top)


- 1) Adjustment legs are stick to the bottom of the machine, when the machine comes out of factory. this condition is ideal for vibration and noise.
- 2) When you install the machine initially or move the machine in use, unscrew the 4 legs to the left and place the machine level and spin the locking nuts and tighten it strongly.



12. Setting up a wash machine.


- 3) Even though adjustment legs came out all the way, if machine is not leveled, prop up the machine with the wood or brick to make it even.

(Do not use fragile material or slippery material such as laminated paper)




12-2-2 The condition of setting up sink(Disassembled Ass'y- Cover Top)

- 1) Spin the adjustment leg to the left and remove them from the front and rear side of the machine.
- 2) Remove the 4 locking nuts from adjustment legs, and put only adjustment legs back whert those were.
- 3) After removing the fixing screws(each on right, left side) from the machine which is behind ass'y- cover top, disassemble the assy-cover top.
- 4) Install the sink.




12. Setting up a wash machine.

12-3. Door Opening Dimension(Slim Model)



- (When The Door Vertically Open)
The distance between door① and the rear side② is 760mm




- (When the door extremely open ※)
The distance between the door edge(①) and the left side of washing machine(②) is 255mm

※ Maximum door angle(③) is 170°

13. Assemble and Disassemble



1. ASSÍ Y-COVER TOP

- 1) Remove two screws fixing the top-cover on back side.
- 2) Push the top-cover back about 15mm and pull it up.
- 3) It's possible to exchange and service Assy-Panel (PCB), the pressure-sensor, the noise-filter, the water valve and trans(option).



2. FRAME FRONT


- 1) Remove the top-cover and the assí y drawer.
- 2) Remove two screws fixing the control-panel on front side and the screw on right side.
- 3) Remove the cover-front(L) by using the (-)driver.
- 4) Pull the lever and open the assí y-door.
- 5) Part the diaphragm and the wire diaphragm away from the frame-front.
- 6) Remove the eight screws fixing the frame-front.
- 7) It's possible to exchange and service the heater, the pump, the shock-absorber and the door lock s/w.



13. Assemble and Disassemble



3. BELT

- 1) Remove the top-cover.
- 2) Disassemble and assemble the belt.
- 3) Check the belt is located at center of the motor-pulley.
<When assemble the belt>
Hook the belt on the motor pulley 1) and place it around the pulley 2).



4. MOTOR

- 1) Lay down the washer on left side.
- 2) Remove the wire housing from the motor.
- 3) Remove the bolt fixing the motor with the box drive on back side.
- 4) Remove the motor.




5. How to Assemble the RELAY Housing.

<CAUTION>

Insert the Relay Housing to the Relays on the opposite direction each other.


[Relay Housing Color]

A	B
WHITE	BLUE




14. Tools for Disassembly and Assembly


NO.	TOOL		
1	Box driver	10mm 13mm 17mm 19mm	Heater (1) Motor (1), Balance (5) 2 holes of each left and right of the shock absorber 1 Pulley hole
2	Double-ended spanner	10, 13 17,19mm	Replaceable for the box driver. Since the bolt runs idle when the box driver is used, use the box driver 17mm.
3	Vice pliers		Tool to protect the idle and abrasion of the bolt for the box driver.
4	Other(Driver, Nipper, Long nose)		General tools for the after service.
5	JIG for the Tub		1 (Disassemble and Assemble)




15. TOP(FRONT) - Exploded View




15. TUB - Exploded View




15. CASE - Exploded View



15. TOP(FRONT) - Exploded View



15. TUB - Exploded View



15. CASE - Exploded View

